
GREEN TUBE GTO



- 1 Sedimentation filter.
 It eliminates from water the particles bigger than 5 micron.
- 2 Active carbon filter.
 It eliminates the chlorine to protect the reverse osmosis membrane.
- 3 Reverse osmois membrane.
 It eliminates up to 98% of impurities and salts.
- Deionizing resin cartridge.
 It removes the residual salts, bringing their concentration to 0 ppm.





POWER FILTER



RGONOMICS







PURE WATER CLEANING SYSTEMS

GT0

Code	APTA40008				
TECHNICAL DATA					
Operating pressure	bar	system pressure (minimum 3 bar)			
Pure water flow	l/min	water supply			
Water in/out connections	GAS	3/4′			
Max. poles length	m	10			
Productivity	m²/h	up to 80			
ELECTRICAL FEATURES					
Power supply	Ph-V-Hz				
Absorbed power	kW	-			
DIMENSIONS & WEIGHT			_		
Weight	Kg	12,7			
Dimensions (LxWxH)	cm	33x28x145			

POLES AND ACCESSORIES

CODE

MODULAR POLES					
		KTRI40280	Kit Quick Lock 10	10 meters carbon fiber modular pole kit - 6 sections of 1.5 m (LCPR40022), 1 section of 0.75 m (LCPR40083)	
		KTRI40281	Kit Quick Lock 16	16 meters carbon fiber modular pole kit - 10 sections of 1.5 m (LCPR40022), 1 section of 0.75 m (LCPR40083)	
Single components included in the	kit			- 10 Sections of 1.3 in (Lot 1440022), 1 Section of 0.73 in (Lot 1440003)	
		1 LCPR40022	carbon fiber 1.5 n	n section (700 g)	
	_0	2 LCPR40083	carbon fiber 0.75	m section with threaded terminal (484 g)	
		3 MPVR40229	caddy		
8		4 TBFX40003	20 m flexible hose with fittings		
6		6 RCVR40107	5 cm adapter for speed brush coupling on plastic gooseneck		
		6 RCVR40053	fitting with gaske	t	
ELESCOPIC POLES					
2 /		LCPR40097	PGG07	6 meters glass fiber telescopic pole kit	
		LCPR40098	PGG12	10.5 meters fusion telescopic pole kit	
		LCPR40099	PGG15	13.5 meters carbon fiber telescopic pole kit	
ngle components included in the k	kit	① LCPR40094	6 m alogo fibor to	leccopie pole for PCCO7 + 20 meters flevible hose (1.6 kg)	
	9	1 LCPR40095	6 m glass fiber telescopic pole for PGG07 + 20 meters flexible hose (1.6 kg) 10.5 m fusion telescopic pole for PGG12 + 20 meters flexible hose (2.8 kg)		
10		1 LCPR40096		er telescopic pole for PGG15 + 20 meters flexible hose (4.4 kg)	
	3	2 RCVR40107		speedbBrush coupling on plastic gooseneck	
		3 RCVR40053	Fitting with gaske		
OOSENECKS					
		RCVR40048	gooseneck with 5 cm angular adjustment (67 g) (RCVR40107 adapter required for speed brush installation)		
		RCVR40070		25 cm angular adjustment (130 g) oter required for speed brush installation)	
LUMINIUM GOOSENECKS					
A A 4		RCVR40104	adjustable 10 cm aluminium gooseneck (192 g)		
The state of the s	1	RCVR40105	adjustable 20 cm	aluminium gooseneck (224 g)	
		RCVR40106	adjustable 40 cm	aluminium gooseneck (269 g)	
LUMINIUM GOOSENECKS FOR DOUBL	E BRUSH				
		RCVR40108	adjustable 10 cm	aluminium gooseneck for 2 brushes of 30 cm joined together (364 g)	
		RCVR40109	adjustable 20 cm	aluminium gooseneck for 2 brushes of 30 cm joined together (342 g)	
	•	RCVR40110	adjustable 40 cm	aluminium gooseneck for 2 brushes of 30 cm joined together (464 g)	

POLES AND ACCESSORIES

CODE

SPEED BRUSH SOFT						
	SPID40006	30 cm nylon brush with 0° nozzles (482 g) for delicate surfaces				
	SPID40007	30 cm nylon brush with 0° and 25° double nozzles (486 g) to better the cleaning operation during rinsing phase				
	SPID40012	50 cm nylon brush with 0° and 25° double nozzles (718 g) to increase the operative productivity				
SPEED BRUSH HARD						
0°	SPID40008	30 cm natural bristles brush with 0° nozzles (352 g) for non-delicate surfaces				
0° 25°	SPID40009	30 cm natural bristles brush with 0° and 25° double nozzles (432 g) to better the cleaning operation during rinsing phase				
BACK SCRUB (REAR WASHING FLEECE SUPPORT)						
	SPPV40029	30 cm washing fleece support Technolite				
	SPPV40030	microtiger: 30 cm microfiber replacement washing fleece to use for a pre-treatment of surfaces to remove the stratified dirt.				
	SPPV40031	FT12: 30 cm microfiber replacement washing fleece with abrasive strip for a pretreatment of surfaces to remove the crusted dirt.				
BATTERIES AND BATTERY CHARGERS						
	BAAC00120	12V 45Ah / C5 battery. running time up to 2 hours				
	BACA00176	5A 12V CBHD1 'stand alone' battery charger				
	BAAC00117	12V 74Ah / C5 battery. running time up to 4 hours				
	BACA00177	10A 12V CBHD2 'stand alone' battery charger				
OTHER ACCESSORIES						
Y	KTRI40112	Y valve for 2 poles installation				
	RCVR40111	plastic T valve - standard on speed brush - optional on applications with double brush				
	PRCH40034	bowder for osmotic membrane filter maintenance (standard equipment) Ideal to preserve the integrity and the functionality of the filtrating meshes from the formation of weeds and moulds that could compromise the correct operation of the filter. to use in view of long periods of inactivity.				
	TBBP40040	flexible hose for telescopic poles and speed brush sold at linear meter				

Warranty

Refer to your local representative for warranty information.