PURE WATER CLEANING SYSTEMS

HIGH PURE HPB



Sedimentation filter. It eliminates from water the particles bigger than 5 micron.

Active carbon filter. It eliminates the chlorine to protect the reverse osmosis membrane.

Reverse osmois membrane. It eliminates up to 98% of impurities and salts.

Deionizing resin cartridge. It removes the residual salts, bringing their concentration to 0 ppm.

STANDARD EQUIPMENT







POWER FILTER

PURE WATER CLEANING SYSTEMS

		НРВ
Code		APTA40016
TECHNICAL DATA		
Operating pressure	bar	4-5
Pure water flow	l/min	2-5
Water in/out connections	GAS	3/4′
Max. poles length	m	16 (also with 2 poles)
Productivity	m²/h	up to 200
ELECTRICAL FEATURES		
Power supply	Ph-V-Hz	1-120-50
Absorbed power	kW	0,14
DIMENSIONS & WEIGHT		
Weight	Kg	35
Dimensions (LxWxH)	cm	53x50x127

POLES AND ACCESSORIES

	CODE		
MODULAR POLES			
	KTRI40280	Kit Quick Lock 10	10 meters carbon fiber modular pole kit - 6 sections of 1.5 m (LCPR40022), 1 section of 0.75 m (LCPR40083
	KTRI40281	Kit Quick Lock 16	16 meters carbon fiber modular pole kit - 10 sections of 1.5 m (LCPR40022), 1 section of 0.75 m (LCPR4008
Single components included in the kit			
	LCPR40022	carbon fiber 1.5 n	
12 million	2 LCPR40083	carbon fiber 0.75	m section with threaded terminal (484 g)
	⁶⁹ MPVR40229	caddy	
	4 TBFX40003	20 m flexible hose	e with fittings
	6 RCVR40107	5 cm adapter for	speed brush coupling on plastic gooseneck
	6 RCVR40053	fitting with gaske	t
ELESCOPIC POLES			
h /h	LCPR40097	PGG07	6 meters glass fiber telescopic pole kit
	LCPR40098	PGG12	10.5 meters fusion telescopic pole kit
ngle components included in the kit	LCPR40099	PGG15	13.5 meters carbon fiber telescopic pole kit
ingle components included in the kit	1 LCPR40094	6 m glass fiber te	lescopic pole for PGG07 + 20 meters flexible hose (1.6 kg)
0 0 0	LCPR40095	10.5 m fusion tele	scopic pole for PGG12 + 20 meters flexible hose (2.8 kg)
	LCPR40096	13.5 m carbon fib	er telescopic pole for PGG15 + 20 meters flexible hose (4.4 kg)
	2 RCVR40107	5 cm adapter for	speedbBrush coupling on plastic gooseneck
	3 RCVR40053	Fitting with gaske	rt
OOSENECKS			
	RCVR40048		5 cm angular adjustment (67 g) oter required for speed brush installation)
	RCVR40070		25 cm angular adjustment (130 g) oter required for speed brush installation)
LUMINIUM GOOSENECKS			
	RCVR40104	adjustable 10 cm	aluminium gooseneck (192 g)
A ST ST ST	RCVR40105	adjustable 20 cm	aluminium gooseneck (224 g)
	RCVR40106	adjustable 40 cm	aluminium gooseneck (269 g)
LUMINIUM GOOSENECKS FOR DOUBLE BRUSH			



RCVR40108	adjustable 10 cm aluminium gooseneck for 2 brushes of 30 cm joined together (364 g)
RCVR40109	adjustable 20 cm aluminium gooseneck for 2 brushes of 30 cm joined together (342 g)
RCVR40110	adiustable 40 cm aluminium gooseneck for 2 brushes of 30 cm joined together (464 g)

POLES AND ACCESSORIES

	CODE	
SPEED BRUSH SOFT		
	SPID40006	30 cm nylon brush with 0° nozzles (482 g) for delicate surfaces
	SPID40007	30 cm nylon brush with 0° and 25° double nozzles (486 g) to better the cleaning operation during rinsing phase
	SPID40012	50 cm nylon brush with 0° and 25° double nozzles (718 g) to increase the operative productivity
SPEED BRUSH HARD		
	SPID40008	30 cm natural bristles brush with 0° nozzles (352 g) for non-delicate surfaces
	SPID40009	30 cm natural bristles brush with 0° and 25° double nozzles (432 g) to better the cleaning operation during rinsing phase
BACK SCRUB (REAR WASHING FLEECE SUPPORT)		
	SPPV40029	30 cm washing fleece support Technolite
	SPPV40030	microtiger: 30 cm microfiber replacement washing fleece to use for a pre-treatment of surfaces to remove the stratified dirt.
	SPPV40031	FT12: 30 cm microfiber replacement washing fleece with abrasive strip for a pre- treatment of surfaces to remove the crusted dirt.
BATTERIES AND BATTERY CHARGERS		
	BAAC00120	12V 45Ah / C5 battery. running time up to 2 hours
	BACA00176	5A 12V CBHD1 'stand alone' battery charger
	BAAC00117	12V 74Ah / C5 battery. running time up to 4 hours
	BACA00177	10A 12V CBHD2 'stand alone' battery charger
DTHER ACCESSORIES		
Y	KTRI40112	Y valve for 2 poles installation
	RCVR40111	plastic T valve - standard on speed brush - optional on applications with double brush
	PRCH40034	bowder for osmotic membrane filter maintenance (standard equipment) Ideal to preserve the integrity and the functionality of the filtrating meshes from the formation of weeds and moulds that could compromise the correct operation of the filte to use in view of long periods of inactivity.
0	TBBP40040	flexible hose for telescopic poles and speed brush sold at linear meter

Warranty

Refer to your local representative for warranty information.

For a demonstration or additional information, call +39 0421 205511 or email info@ipcleaning.com

IP Cleaning S.p.A. Viale Treviso 63 30026 Summaga di Portogruaro - (VE) / ITALY Tel. +39 0421 205511 - Fax +39 0421 204227 info@ipcleaning.com - www.ipcleaning.com Rights to technical modifications reserved without prior notes.