



SCRUBBER DRIERS - WALK BEHIND

# CT46

MAX PRODUCTIVITY

1750 m<sup>2</sup>/h

BATTERIES  
RUNNING TIME

3 h

WATER TANK  
RUNNING TIME

50'  
working session



### MOST FREQUENTLY USE



### INNOVATIONS



ECO  
SELECT



DBL™  
DOUBLE  
BATTERY  
LIFE



UDC™  
ULTIMATE  
DRAIN  
COMBO



SLS™  
SELF  
LEVELING  
SYSTEM



ANC™  
ADVANCED  
NOISE  
CONTROL

### SPECS



FOLDABLE HANDLE



LARGE BATTERY BOX



PATENTED TRANSPORT WHEEL

## TECHNICAL DATA

		<b>CT46 B50</b>	<b>CT46 C50</b>
Code		LPTB01802	LPTE00642
<b>PERFORMANCE</b>			
Max theoretical productivity	m <sup>2</sup> /h	1750	1750
Cleaning path	mm	500	500
Water tank capacity (solution recovery)	l	40/46	40/46
Max running time	min	180	Unlimited
Voltage	V-Ah	24(2x12)-105 GEL	230-50/60
Installed power	W	910	950
Brush pressure	kg	16/25	16/25
Squeegee width	mm	730	730
Max speed	km/h	3,5	3,5
Weight	kg	120	68
Dimension (LxWxH)	mm	855x580x1220	855x580x1220

## STANDARD ACCESSORIES

	<b>CT46 B50</b>	<b>CT46 C50</b>
<b>BRUSHES</b>		
BRUSH	SPPV01332	SPPV01332
<b>SQUEEGEE BLADES</b>		
LATEX FRONT BLADE	MPVR06287 - 815mm	MPVR06287 - 815mm
LATEX REAR BLADE	MPVR06288 - 715mm	MPVR06288 - 715mm

## CONSUMABLES (Codes available on price list)



## OPTIONAL ACCESSORIES



## BATTERIES AND BATTERY CHARGERS

<b>BATTERIES</b>	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	<b>BATTERY CHARGERS</b>
IPC gel battery BAAC00105	2	12V 105 Ah [ C5 ]	345x170x285	180 min	Stand alone high frequency BLS010 - BACA00133 On board battery charger 24V 15 Ah - KTRI0480
EXIDE gel battery BAAC00024	2	12V 105 Ah [ C5 ]	345x174x283	180 min	Stand alone high frequency BLS010 - BACA00133 On board battery charger 24V 15 Ah - KTRI0480
Acid tubular plate BAAC00136	2	12V 85 Ah [ C5 ]	308x175x225	190 min	Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah - BACA00060 On board battery charger 24V 15 Ah - KTRI0480
EXIDE gel battery BAAC00124	2	12V 63 Ah [ C5 ]	261x171x210	180 min	Stand alone high frequency BLS010 - BACA00133 On board battery charger 24V 15 Ah - KTRI0480
Acid tubular plate BAAC00070	2	12V 118 Ah [ C5 ]	345x170x285	190 min	Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12 Ah - BACA00060 On board battery charger 24V 15 Ah - KTRI0480