

HIGH PRESSURE WASHERS - HOT WATER

PW-H100 HTM



PRESSURE

200 bar

FLOW RATE

900

l/h

ABSORBED POWER

6,4 kw

EXCLUSIVE CHARACTERISTICS

- DELAYED TOTAL STOP DTS
- IGNITION BOILER DELAY IBD
- ELECTRONIC TEMPERATURE
 STABILIZER ETSC
- INTELLIGENT AUTOMATIC
 SWITCH OFF IASF
- MICRO LEAKAGE CONTROL - MLC
- DRY RUNNING PROTECTION - DRP
- NOZZLE CLOGGED CONTROL - NCC
- LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ANTISCALE LEVEL CONTROL - ALC
- WORKING HOURS COUNTER - WHC
- MAINTENANCE CHECK LED - MCL
- INFRARED FLAME TEMPERATURE CONTRLOLS - FCS
- HIGH BRIGHTNESS LED SIGNALS - HBLS

MOST FREQUENTLY USE

AGRICOLTURE/FARMING

AUTOMOTIVE

CONSTRUCTION

RETAIL

LOGISTICS AND TRANSPORT

INDUSTRY

COMMUNITIES

WASTE MANEGEMENT





SPECIAL MACHINE: 100°C MAX TEMPERATURE, BOTH HIGH AND LOW PRESSURE MODE

(WITH NO-MARKING RUBBER WHEELS / 3 WHEELS)

INNOVATIONS







IPC PUMP

MODULA BUILD-U

IPC'S EXCLUSIVE BOILER

ANTI-SCALE

SPECS



WARNING LAMP INFORMS WHEN TEMPERATURE IS BETWEEN 90-100°C



PRESSURE REGULATING UNLOADER VALVE BOLT-ON TYPE



COMPLETE WITH NON MARKING WHEELS FOR FLAT SURFACED

TECHNICAL DATA

3 WHEELS PW-H100HT D2015P T

Code		IDAC41248
PERFORMANCE		
Operating pressure	bar/Mpa	30-200/3-20
Flow rate	l/h	450-900
Outlet water temperature	°C	100
Power supply	Ph-V-Hz	3-400-50/13
Absorbed power	kW	6.4
Motor pole / rpm		4-1400
Remote control		DTS
Pump/head/pistons		lpc plunger/brass/ceramic
Boiler thermal power	kW	100
Fuel consumption	Kg/h	7.4
Fuel tank	l	25
Detergent tank	l	22
Detergent delivery		High pressure
Dimensions (LxWxH)	cm	110x70x90
Weight	Kg	140

STANDARD EQUIPMENT









CODE: UGLN07790 L.P. NOZZLE 1/4 2513



CODE: TBAP40237 H.P. HOSE 10MT 1/4" (NO-MARKING)



OPTIONAL ACCESSORIES

CODE: KTRI40341 HOSE REEL KIT



CODE: RCIN10810 HOSE COUPLING M22



CODE: LCLC41140 LANCE FOR WSHING FLOORS INOX

IG CODE: PRCH40039 IG ANTISCALE TREATMENT M421 1KgX6



CODE: PRCH40040 ANTISCALE TREATMENT M421 10Kg



CODE: KTRI40568 MAINTENANCE KIT 500H



