TOOL PRO WDA 40 L / L AS

VACUUM CLEANERS WITH AUTOMATIC FILTER CLEANING

Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for L class dust. It is specifically designed to work in environments characterized by the presence of simple dust at moderate risk. Compact and manageable, TOOL PRO WDA 40 L is ideal for use in environments such as workshops and artisan laboratories. The innovative NONSTOP-VAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Equipped with the power outlet for electric tool (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional). TOOL PRO WDA 40 L is available in two different versions: with antistatic accessories supplied (L AS version), to protect against any electrostatic charges that may occur during work, and with non-antistatic accessories (L version).





Compact and manageable



Pivoting wheels with brake



Hooks for accessories and cable holder



Power tool connection



NONSTOPVAC!

REF. NO. 13101710001

13201710001



PTFE flat filter

8

8

PIECES/PALLET



Antistatic accessories (standard for L AS version)



COMBI Kit (optional)

DECEMBER 1 THE NAME OF THE PARTICULAR PROPERTY O

| I HODOUT IDENTIFICATION | |
|-------------------------|--|
| TYPE | |
| TOOL PRO WDA 40 L | |
| TOOL PRO WDA 40 L AS | |

TECHNICAL DATA

| Voltage - Frequency | 220-240 V~ 50 | /60 Hz | |
|-------------------------------------|---------------------|---------------------------------------|--|
| Max power rating | W | 1350 | |
| Rated power (nominal power) | W | 1100 | |
| Max power of electrical socket load | W | 2400 | |
| Main filter | PTFE flat filter (N | PTFE flat filter (M filtration class) | |
| Filtering surface (flat filter) | m² | 0,5 | |
| Filter cleaning system | | NONSTOPVAC! | |
| Air flow rate | I/s | 76 | |
| Vacuum | mbar | 250 | |
| Container capacity | | 41 | |
| Useful capacity | | 26 | |
| Useful dust bag capacity | | 20 | |
| IP code | | IPX4 | |
| Filtration class | | L | |
| Accessories Diameter | mm | 33 | |
| Power supply cable | m | 7 | |
| Weight (without accessories) | Kg | 21 | |
| Dimensions | mm | 625x385x545 | |

| CTANDADD | ACCESSORIES |
|-----------------|--------------------|
| SIANDAUD | ACCESSURIES |

| TYPE | REF. NO. |
|--|----------|
| Flexible hose Ø 33 - 4 m (*) | 6010533 |
| Antistatic flexible hose Ø 33 - 4 m (**) | 6010530 |
| Chromed extension tube 0,5 m (***) | 2511500 |
| Dry floor tool P340 Ø 36 (*) | 6010041 |
| Antistatic dry floor tool P340 Ø 36 (**) | 6010042 |
| Connection Ø 33 (*) | 2511405 |
| Antistatic connection Ø 33 (**) | 2511406 |
| Crevice tool Ø 36 (*) | 2511520 |
| Antistatic crevice tool Ø 36 (**) | 2511640 |
| Front intake cap | 2001817 |
| PTFE flat filter (M filtration class) | 2512772 |
| Fleece filter bag (I 20) | |
| | |

OPTIONAL ACCESSORIES

| OI IIOIIAE AGGEGGGIIIEG | |
|--|----------|
| TYPE | REF. NO. |
| Antistatic flexible hose Ø 29 - 4 m (**) | 6010531 |
| Flexible hose Ø 38 - 4 m | 6010536 |
| Squeegee tool V340 Ø 36 | 6010046 |
| COMBI Kit | 6689163 |
| Remote Control Kit | 6689165 |
| Tool box adaptors | 6689164 |
| Transport handle | 6340100 |
| PE bag | 3001203 |
| Fleece filter bag I 20 x 10 | 3001039 |





^(*) For L version (**) For L AS version (***) 2 on standard equipment